

Chain Welding Machine for Resistance Butt Welding of Round Steel Chains



KEH 8

KEH 8 – Back side

▼ KEH 8 – Front side



Our Accomplishments for your Benefit

- Robust machine design for the production of highstrength chains over a long period of time
- Continuous welding of all chain links in one cycle
- Complete deburring of welding burr
- Frequently copied but never matched



Design Features

- Drive system:
- Servomotor
- Complete deburring of welding burr takes place in two cycles: transverse deburring and longitudinal deburring. This ensures an optimum chain link surface without deburring residue.
- Safety devices for protecting tools and machine parts.
- Upper part of the machine can be swiveled backward to ensure optimum tool accessibility.

KEH 8 – Hydraulic power unit



Quality, Reliability, and Efficiency – WAFIOS KEH 8 Chain Welding Machine

Application

KEH-series chain welding machines are used for the resistance butt welding of bent round steel chains with notching on the chain link ends. The welding burr on the chain link is completely deburred by the chain welding machine.



▲ Set of tools for KEH

Quality

For more than 125 years, the name of WAFIOS has been synonymous with highest quality, safety standards, and technical innovations in the German machine manufacturing industry.

Reliability

Strict quality controls, state-of-the-art production systems, and many years of experience guarantee that your investment is safe in our hands. Our global service network ensures high availability of WAFIOS machinery.

Efficiency

High production output and a long service life will save money and shorten the amortization time of your investment.

Set of tools for KEH 8



WAFIOS KEH 8 Chain Welding Maschine 3

WAFIOS **[]**

Technical Data		KEH 8
Wire diameter:		13.0-20.0 mm
Welded chain link:	/ Pitch inside link length	32.0–130.0 mm min. 2.7 × d
Output:		27–14 links/min
Power installed:		27.4 kW
Welding transformer:	rated power at 50% duty cycle connected load	315 kVA 450 kVA
Compressed air requirement:	(l/cycle at 6 bar)	0,5 l/cycle
Cooling water consumption:	(l/min at 3 bar)	35 l/min at 4 bar
Hydraulic system tank contents:		630 Liter
Space required:	(lxwxh)	abt. 5,500 × 4,00
Net weight:		
	Machine Switch cabinet Hydraulic system	abt. 9,000 kg abt. 400 kg abt. 1,700 kg





min. 2.7 × d 27 –14 links/min 27.4 kW 315 kVA 450 kVA 0,5 l/cycle 35 l/min at 4 bar 630 Liter abt. 5,500 × 4,000 × 2,750 mm abt. 9,000 kg abt. 400 kg abt. 1,700 kg

Our product range includes a wide variety of high-quality chain machines.

- Chain bending machines, KEB x.1 and KEB x.2 series
- Chain bending machines, KER x.2 and KER 8 series
- KBA 601 chain bending machine with conduction (WED 601) heating or with induction (IEW 601) heating of chain link blanks
 Chain bending machine KBF 60
- with induction heating (IEW 60) of chain link blanks
- Chain (resistance butt) welding machines, KEH x.2 and KEH 8 series
- Chain (flash butt) welding machines, KSH and KSF 60 series
- Chain calibrating machines, KPH series

WAFIOS AG

Silberburgstraße 5 72764 Reutlingen, Germany Phone +497121 146-0 Fax +497121 146-250 sales@wafios.de www.wafios.com

Machinery for Wire and Tube