

Stand-Alone Wire Feeder

WAFIOS AG now offers a newly developed stand-alone wire feeder to support the feeding and removing of wire to and from the machine. The benefits are shorter setup times and a safer working environment for the operators.

■ Our Accomplishments for your Benefit

- ✓ Shorter setup times when changing coils
- ✓ Safer working conditions when changing coils and feeding the wire into the machine
- ✓ Lower costs due to easier material handling
- ✓ Easier handling of larger sized wire
- ✓ Better operator safety when removing and strapping leftover coils
- ✓ As a stand-alone device not tied to a certain machine type (hydraulic aggregate as an option)

■ Technical Specifications

- Wire size (standard range): 14 - 28mm (0.55118in - 1.1024in)
- Height of wire line (hydraulically adjustable): 960 - 1.450mm (37.795in - 57.087in)
- Feed rate: max. 30m/ min, infinitely variable
- Feed motor output: 4kW
- Feed roller pressure (hydraulically): max. 37kN



■ Operation

- Feed and remove different sized wire
- The height is hydraulically adjustable to match the wire line
- The feed unit can be pivoted to match the angle of the wire
- Wire feed with 3 sets of feed rollers, frequency-controlled by an asynchronous motor
- Operates with an independent PLC and control panel

Your Contact:

Mr. Martin Baumann - Customer Service
 Tel.: +49 (0)7121 / 146 218
 Fax: +49 (0)7121 / 146 1301
 Mail: baumann@wafios.de

